



Hole Dimensions: The hole should be dug 2' wider and 2' longer than the external dimensions of the tank. The bottom should be leveled with 4" of graded material in the bottom.

Access for Delivery Truck: Access to the hole is the responsibility of the property owner/contractor. We use a knuckle boom rig to deliver and set the tanks. The area in front and around the hole must be flat and clear of fill and debris. The road to the hole must be solid and level.

Water Concerns: Our tanks are water tight structures. Excessive amounts of water must be removed from the hole before the tank can be set properly. If you are working below the water table, it is recommended that you immediately fill the tank with water to a minimum 3/4 full to prevent tank from floating. It is the purchasers responsibility to ensure that these steps are followed. a reset fee will be charged for any additional site visits.

Backfilling: The hole should be backfilled as soon as possible with low graded material, ie. no large stones.

Waiting Time: There will be a charge of \$65.00 per hour for each hour or any portion of an hour after the first hour of time spent on the site. It is to your advantage to see that the site is properly prepared before delivery time is set.

Plumbing Works: All plumbing works to the tank will be responsibility of the purchaser.

Tanks in Traffic Areas: A custom lid will be required if the tank will be placed in an area of vehicles. The original lid design is for non-vehicle traffic only.

Holding Tank Accessories

Porthole Covers, 4" and 8" Extension/Riser Rings

HOLDING TANKS					
CAPACITY	A	B	C	E	PRICES
2000 gal	80"	143"	68"	26"	\$ 2,500.00
1500 gal	68"	151"	60"	26"	\$ 1,900.00
1000 gal	80"	84"	68"	26"	\$ 1,400.00
650 gal	80"	60"	68"	26"	\$ 900.00
500 gal	68"	52"	60"	26"	\$ 750.00

** Additional charges for delivery \$125.00(GT) \$150.00(Sav./WB) \$175.00(BT to FS) \$200.00 (EE, NS, RP)



P.O.Box 10587 APO, Grand Cayman
Cayman Island

HOLDING TANKS

DRAWN BY: FSS

CHECKED BY: MJ/JP

SCALE: NTS

Phone: 945-8495
Fax: 945-4808
Email: info@ciprecast.com.ky